

Universal-Lautsprecher RSU

Universal Loudspeaker



RSUA



RSUU



RSUK

Modulares Lautsprechersystem RSU

Dieser universell einsetzbare Gehäuselautsprecher besteht nicht nur durch sein zeitloses Design, sondern auch durch seine ausgezeichnete Tonqualität. Er ist in den Farben weiß, schwarz und braun erhältlich. Eingebautes Breitbandssystem mit integriertem Hochtonkegel, 6 Watt Übertrager für 100V und 50V lieferbar. Durch den von Uniton entwickelten modularen Aufbau kann der Lautsprecher sowohl als Gehäuselautsprecher als auch als Wand- oder Deckeneinbaulautsprecher verwendet werden. Einfache Wandmontage, Anschluss über Anschluss-klemme. Mittels Konsole ist auch die seitliche Montage möglich.

RSU Modular Loudspeaker Systems

A universal cabinet speaker, it's impressive timeless design is complemented by its outstanding acoustic quality. Comes with built-in broad-band system, integrated tweeter dome and choice of 6 Watt 100V or 50V transformer. The modular design developed by Uniton makes the speaker suitable for cabinet or recessed wall and ceiling applications. Mounts easily to walls and connects via connecting terminal. Can also be side-mounted by means of a wall or ceiling bracket.

Universal-Lautsprecher RSU Universal Loudspeaker

Technische Daten für RSU - Lautsprecher

Technical specifications RSU - loudspeakers

Leistung	Power	6 / 9 Watt
Frequenzgang (-3dB)	Frequency range (-3dB)	80 - 16000 Hz
Schalldruck SPL (1W / 1m)	Sound pressure (1W / 1m)	90 dB
Schalldruck SPL max.	Sound pressure (max.)	97 dB
Gewicht mit Übertrager	Weight with transformer	1,35 kg
Impedanz	Impedance	4 Ohm
Abmessungen	Dimensions (L x W x H)	220 x 220 x 80 mm
100 V / 6 W Übertrager mit folgenden Anpassungen:	Built-in 100 V 6 W transformer with tapings:	6 3 1,5 Watt 1660 3300 6600 Ohm

Folgende Varianten sind erhältlich:

- ohne Übertrager 4 Ohm / 6 W
- mit 100 V / 6 W Übertrager
- mit 50 V / 6 W Übertrager
- mit 15/25 Watt HiFi-Lautsprecherchassis
- mit eingebautem L-Regler
- Farbe: weiß, schwarz, braun

RSUA-T Aufbau Lautsprecher mit 100V / 6W Übertrager

Abmessungen L x B x H:
Art. Nr. weiß:
Art. Nr. schwarz:
Art. Nr. braun:

RSUU-T Einbaulautsprecher mit 100V / 6W Übertrager

Einbauloch:
Abmessungen L x B x H:
Einbauhöhe sichtbar:
Art. Nr. weiß:
Art. Nr. schwarz:
Art. Nr. braun:

RSUK-T Konsolenlautsprecher mit 100V / 6W Übertrager

Abmessungen L x B x H:
Konsolenlänge: 60 mm und 120 mm lieferbar
Art. Nr. weiß:
Art. Nr. schwarz:
Art. Nr. braun:

The following options are available:

- without transformer, 4 Ohm / 6 W
- with 100 V / 6 W transformer
- with 50 V / 6 W transformer
- with 15/25 Watt hifi loudspeaker
- with volume control
- Color: black, white, brown

RSUA-T Surface mount speaker with 100 V / 6 W transformer

Dimensions L x W x H:
Article No. white:
Article No. black:
Article No. brown:

220 x 220 x 80 mm
2.100.107.09
2.100.107.00
2.100.107.01

RSUU-T Recessed speaker with 100 V / 6 W transformer

Recess:
Dimensions L x W x H:
Projection from surface:
Article No. white:
Article No. black:
Article No. brown:

ø 185 mm
220 x 220 x 60 mm
40 mm
2.100.102.09
2.100.102.00
2.100.102.01

RSUK-T Model with bracket and 100V / 6W transformer

Dimensions L x W x H:
Bracket length:
Article No. white:
Article No. black:
Article No. brown:

220 x 220 x 80 mm
60 or 120 mm
2.100.110.09
2.100.110.00
2.100.110.01

D0406AW / 0.950.719.00 / Technische Änderungen vorbehalten / We reserve the right to make technical changes.

